



Terminal	
No.	Pin Name
1	FLM
2	LP
3	CP
4	M
5	V0
6	VDD
7	VSS
8	VOUT
9	XD0
10	XD1
11	XD2
12	XD3
13	/DISPOFF
14	NC
15	BLA
16	BLK




Pixels Details
Scale=30/1



Wiring Details(Top View)
Scale=Free

Note:

- *1. Display Type : FSTN, Positive, Transmissive
- *2. Viewing Direction : 6H
- *3. Duty : 1/240, Bias : 1/14
- *4. Backlight Color : White
- *5. Backlight Supply : 170mA(3.3V TYP.)
- *6. Operating Voltage : 3.0 ~ 5.0V
- *7. Operating Temperature : -20°C~70°C
- *8. Storage Temperature : -30°C~80°C
- *9. An external VR(25K to 50K) must be connected for Contrast Control



Backlight Circuit
(No. of LEDs = 10pcs)
Scale=free

C		
B		
A		
Rev	Note	Date
Dwg Title LM320240BCW Outline Dwg		
Dwg No.	MK-002501-1-1	Date 2008-06-03
Scale 6/5	Tol. \pm 0.5	Unit mm Paper Size A3
Approved	Checked	Drawn Zhou Huifang

TOPWAY