



Pin	Symbol
1	NC
2	VSDH
3	VDDH
4	VSSH
5	IRBE
6	OSCA3
7	OSCA1
8	VDDIO
9	CPU
10	PS
11	D15
12	D14
13	D13
14	D12
15	D11
16	D10
17	D9
18	D8
19	D7
20	D6
21	D5
22	D4
23	D3
24	D2
25	D1
26	D0
27	RS
28	CSB
29	RDB
30	WRB
31	RESETB
32	VSS
33	VDD
34	VSSH
35	VDDH
36	VSDH
37	NC

- Notes:
1. Driver IC: SEPS645
 2. COF Number: SEPS645F01
FPC Number: UT-0864-P01
 3. Interface:
8-/16-bit 68XX/80XX Parallel, 4-wire SPI
 4. The film terminal use "Sn Plating"
 5. General Tolerance: ±0.30
 6. The total thickness (1.77 Max) is without Polarizer Protective film & Remove tape.
The actual assembled total thickness with above materials should be 1.92 Max

Customer Approval <i>Signature</i>		Univision Technology Inc.				Drawing Number DHE2076SDPF02		Rev. A	
Unless Otherwise Specified		Title		U-G-2076GDEAF02 Folding Type OEL Display Module		Material		Soda Lime / Polyimide	
Unit		mm		Pixel Number: 220 (RGB) x 176, 262144 Color, COF Package		Scale		Sheet	
General Roughness		Tolerance		By		Date		Sheet	
±		±0.3		Kirin Zhuang		20060911		1 of 1	
Angle		±1		Jerry Wang		20060911		A3	
				Panel / E.		E.E		Migrant Chang	
				Date		20060911		Scale	
				Date		20060911		Sheet	
				Date		20060911		Size	

Item	Date	Remark
A	20060911	Original Drawing