



### 3.Outline dimension

NO.	SYMBOL	HL	SYMBOL	HL
1	AGND	31	VSD	
2	AVDD	32	MODE3	
3	VCC	33	RSTB	
4	RO	34	STBYB	
5	R1	35	SHLR	
6	R2	36	VCC	
7	R3	37	UPDN	
8	R4	38	GND	
9	R5	39	AGND	
10	R6	40	AVDD	
11	R7	41	VCLMin	
12	G0	42	DITH	
13	G1	43	NC	
14	G2	44	NC	
15	G3	45	V10	
16	G4	46	V9	
17	G5	47	V8	
18	G6	48	V7	
19	G7	49	V6	
20	R0	50	V5	
21	B1	51	V4	
22	B2	52	V3	
23	B3	53	V2	
24	B4	54	V1	
25	B5	55	NC	
26	B6	56	VGH	
27	B7	57	VCC	
28	DCLK	58	VGL	
29	DE	59	GND	
30	HSD	60	NC	

  

NOTES:

1. Display mode: Transmissive
2. Interface type: System parallel
3. Viewing direction: 6:00
4. Driver IC: ILIS480+IL6123H (S)
5. Input voltage: 3.0~3.6V
6. Backlight: White LED(3x8LED parallel)  
If=160mA Vf=9.6V
7. Operating temperature: -20°C ~ +70°C
8. Storage temperature: -30°C ~ +80°C
9. Interface connector: FPC
10. Request ROHS

  

LED CIRCUIT DIAGRAM

  

Rev.	Revision content description	Date
A	FIRST ISSUE	2013.9.3

  

	深圳市如新电子有限公司				
	TOLERANCE (公差)	Mod. Name	PART Name		
TOLERANCE UNLESS OTHERWISE SPECIFIED	X.XX±0.3	IVO062-01	LCM		
UNIT	DESIGNED(structure)	DESIGNED(election)	APPROVED		DRAWING NAME
mm	JHJ				ASSEMBLE